FREIGHTMASTER

SEMI TRAILERS

CURTAINSIDER SEMI TRAILERS

Proudly built & manufactured in South Australia since 1986





Specifications

Model: ST2/ST3—Flat Tops & Drop Decks

Road Train & B Double Specs

Dimensions: 'A' Trailer 20' (6.09m) - 28' (8.53m)

'B' Trailer 41' (12.5m) - 48' (14.6m)

Construction: 12mm Top Flange - Grade 350 steel 20mm Bottom Flange - Grade 350 steel

5mm Webb with 8mm over goose neck

- Heavy Duty 20mm top/25mm bottom - optional- 5mm Webb with 10mm over goose neck - optional

Coaming: 100 x 45 TFB

- 125 x 64 TFB optional

Flooring: 2.3mm steel Checker plate - 9 floor runners Skid Plate: 10mm thick with 50mm bolt in King Pin

(Road Train Rated)

Braking System: Knorr-Bremse Air Brake with Yard release

Landing Legs: Jost T520 2-speed legs

Axles: 125mm round York cast spoke hubs

enclosed 'S' cams-grease or oil filled

- BPW, TMC etc optional

Suspension: York Tapered Bush cast suspension 8 leaf springs

- Airbag optional

Toolbox: One steel lockable

Tyre Carrier: Drop Deck cut through main beam

Flat Top dual bolt on

Lighting: All HELLA LED to full ADR requirements

- 6mm wiring optional

Nose Cone: Full length & width - fibreglass

Rear Doors: 20mm Fibreglass with 5 hinges, 4 locking bars & anti

rattle bar

Double Stacker: 4,6,& 8 pallets up to 4000kg





www.freightmastertrailers.com.au Email: admin@freightmastertrailers.com.au







AGENT: