## FREIGHTMASTER®

## HARDOX TIPPING TRAILERS

Proudly built & manufactured in South Australia since 1986



## **Specifications**

Model: ST2/ST3/ST4

Road Train & B Double Specs
Dimensions: 26' (7.9m) - 33' (10.1m) - Chassis

Max width - 2500mm

Height - 900mm - 2400mm

Construction: Fabricated 'I' Beam
(Chassis) 100 x 16mm Top Flange
100 x 20mm Bottom Flange

5mm Webb - Grade 350 Steel 100 x 100 x 6 RHS Subframe

Construction: 100 x 100 x 6 RHS Subframe (TOA) 100 x 75 x 6 RHS 2 piece Draw Arms

Tub Construction: Standard floor - 6mm grade 450 Standard Wall - 4mm grade 450

Options available

Skid Plate: 10mm thick with bolt in King Pin - Chassis Braking System: Knorr-Bremse Air Brake with Yard release

Landing Legs: Jost T520 two speed Pad Feet

Axles: York 5" round Spoke Hubs - Enclosed 'S' Cams

Grease/Oil filled

Optional - 10 Stud & Disc (BPW, TMC)

Suspension: York Tapered Bush cast with 8 Leaf Springs

Optional: 3 Leaf Springs - Airbag York/BPW

Hoist: Binotto 4 & 5 stage 50 tonne

Tyre Carrier: Dual bolt-on to underside

**Lighting:** One piece wiring loom complete with

HELLA LED jumbo rear & side lights

to ADR requirements - 6mm wiring Road Train Roll Tarp, Extension Sides, Bagging Door,

Options:

Way Tailgate, side swing Tailgate with cam locks

Heavy Duty bracing on walls



## **CHASSIS TIPPERS**













www.freightmastertrailers.com.au Email: admin@freightmastertrailers.com.au